

## 800 JAW CRUSHER

### STANDARD FEATURES

- Single toggle jaw crusher
- Hydraulic jaw wedge adjustment
- Hydraulic adjustable C.S.S
- Hydraulic drive via 6 SPC V belts
- Crusher RPM 275-320  
(depending on application)
- Two-piece side cheek plates
- Std jaw plate 18% Mn (tall tooth profile)
- Optional jaw plate 18% Mn (corrugated profile)
- High strength frame
  - Four-piece bolted and welded construction
  - Cast steel front and rear sections
  - High strength structural steel side sections
  - Machined jaw die support faces
- Reversible corrugated jaw dies
  - Full height stationary jaw die
  - Lift holes cast into jaw die
  - Extended jaw die frame protection
- Robust swing jaw action
- Left hand flywheel grooved for V-belt drive
- Bolt-on support feet
- Additional options available upon request



### OVERVIEW

Feed opening: 800 x 500mm

Min Jaw Setting: 25mm

Max Jaw Setting: 125mm

Weight: 8,000 kg

**FOR FURTHER INFORMATION AND SALES ENQUIRIES CONTACT:**

**NICK TAYLOR - SALES DIRECTOR**

E-mail: [sales@giantcrusher.com](mailto:sales@giantcrusher.com)

Phone: 0800 086 8776